

Date of impression 30.04.2018/13:14:10
page/of 1/1

edition 07.02.2018

material denomination **STAPA IL HYDROLAN S 412 Aluminium Paste**

material-no. 022577ZZ3

material description Pigmentpaste of flaky aluminiumpowder produced of pure aluminium min. 99,5 % EN 576, with an inorganic coating

Specific gravity app. 1,2 kg/l

The solvent contained is isopropanol (IL) including lubricant and additives.

Pigmentcomposition:

aluminium app. 42,5%

coating app. 7,5%

insp. characteristic	specification	unit
TI00004 pigment content / non volatile	48,0 - 52,0	%
TI00004 volatile content	48,0 - 52,0	%
TI00005 sieving < 40 µm	99,9 - 100,0	%
TI00009 D 10	6,0 - 9,0	µm
TI00009 D 50	10,0 - 15,0	µm
TI00009 D 90	18,0 - 22,0	µm
TI00033 aqueous paint spray-out	O.K.	

total shelf life in month: 24

EC-safety data sheet-no. 022577ZZ3

The Data on this technical information sheet correspond with the current status of our knowledge and experience.

The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.

We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

quality control department

This document has been printed automatically and will not be signed.